

# HLP-1X1000-US/JP/EU Portable Power Station

Haier



Stable and safe,  
convenient charging and discharging



## Safe

LFP cell 4 common scenarios safety guarantee & 6 stages protection design



## Convenient

Up to 12 output interfaces, supporting simultaneous use of multiple devices





## Reliable

Pure sine wave output, no damage to electrical appliances



## Durable

>2000 life cycles

Model	HLP-1X1000-US	HLP-1X1000-JP	HLP-1X1000-EU
Picture			
Cell type	LFP		
Nominal energy	1182 Wh		
<b>AC output</b>			
AC output	1000 W (1500 W peak)		
Continuous output power	100 - 120 V (pure sine wave)	100 - 120 V (pure sine wave)	200 - 240 V (pure sine wave)
<b>DC output</b>			
DC output	12 ± 1 V / 10 A		
USB A1&A2 output	5 V / 2.4 A		
USB A3&A4 18W output	5 ~ 12 V / 18 W max		
PD 60W output	5 ~ 20 V / 60 W max		
Cigarette lighter socket	13 ± 1 V / 10 A max		
<b>AC / CIG / PV input</b>			
PV input	MPPT 15 ~ 40 V, 12A / 180 W Max		
Cigarette lighter socket	12 ~ 24 V, 10A / 120 W Max		
AC input	100 ~ 120 V; 50 / 60 Hz		
<b>General data</b>			
Protection rating	IP21		
Life cycle	> 2000 times		
DOD	> 90%		
Total output ports	12		
UPS	< 20 ms		
Net weight	23 kg		
Dimension	350 * 345 * 315		
Certifications	CE-EMC/CE-LVD, ROHS, FCC SDOC, UL2743, PSE-EMC/PSE-LVD, UN38.3		

\*All rights reserved. Subject to change without notice.